



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Switch
Device presentation	Mechanism
Switch function	2-pole 1-way
Colour tint	Graphite

Complementary

Rated current	16 AX, 250 V AC, 50/60 Hz
Electrical durability	5000 cycles
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	1 module
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² (rigid) 0...4 mm ² (flexible)
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Marking	ON
Fixing mode	Clip-in
Width	22.5 mm
Height	45 mm
Depth	33 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Embedding depth	21 mm
Product weight	0.026 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	LV directive EN 60669-1 EMC directive

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Acetone Oil Bleach Alcohol Window-cleaning fluid Petrol Liquid soap UV resistant Ammonia
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------