



Main

Range	Unica
Range of product	Unica
Device application	Control
Product or component type	Cord push-button switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	1-way
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Cord push-button
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Graphite

Complementary

Cable length	1 m
Load current	10 A
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm ² (flexible) 2.5 mm ² (rigid)
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _n , cos phi: 0.3
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Standards	EMC directive LV directive EN 60669-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	45 mm
Height	45 mm
Product weight	0.0291 kg
Market segment	Small commercial Residential

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Window-cleaning fluid UV resistant Petrol Alcohol Oil Bleach Liquid soap Ammonia
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------