



Main

| | |
|---------------------------|-------------------------|
| Range of product | Unica |
| Range | Unica |
| Aesthetic name | Unica Top - Unica Class |
| Device application | Control |
| Product or component type | Switch |
| Device presentation | Mechanism |
| Switch function | 1-pole 1-way |
| Colour tint | Graphite |

Complementary

| | |
|--------------------------------|---|
| Rated current | 32 A, 250 V AC, 50/60 Hz |
| Maximum switching current | 25 mA |
| Electrical durability | 10000 cycles (cos phi: 0.6) |
| Insulation resistance | > 5 MOhm @500 V |
| Dielectric strength | 2000 V |
| Minimum load breaking capacity | 200 operations 1.25 In and 1.1 Un, cos phi: 0.3 |
| Opening distance | > 3 mm |
| Actuator | Rocker |
| Number of modules | 2 modules |
| Connections - terminals | Screw terminals |
| Cable cross section | 0...6 mm ² (flexible) 0...6 mm ² (rigid) |
| Material | Mechanism cover : ABS (acrylonitrile butadiene-styrene) |
| Surface finish | Untreated |
| Fixing mode | Clip-in |
| Width | 45 mm |
| Height | 45 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------------------------|---|
| Depth | 32 mm |
| Embedding depth | 20 mm |
| Product weight | 0.039 kg |
| Ambient air temperature for operation | 25...35 °C |
| Ambient air temperature for storage | 0...50 °C |
| Standards | EMC directive EN 60669-1 LV directive |

Environment

| | |
|---------------------------------|--|
| IP degree of protection | IP20 |
| IK degree of protection | IK01 |
| Environmental characteristic | Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid |
| Environmental health and issues | Halogen free |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0622 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|