



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device application	Communication
Device presentation	Mechanism with central plate
Colour tint	Graphite
Data socket type	RJ45 - 4 contacts - category 5e - transmission rate < 155 MHz
Provided equipment	Protective flap Label holder

### Complementary

Communication network type	1000BASE-T
Communication port protocol	ATM 155 Mbps
Product destination	Duct Floor box
Number of modules	1 module
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/UTP
Organization of wire	Unshielded twisted pair
Connections - terminals	Click
Device mounting	Flush
Fixing mode	For shield : by clips Clip-in
Installation direction	Straight
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	22.5 mm
Height	45 mm
Embedding depth	25 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Liquid soap Acetone Petrol Alcohol Oil Window-cleaning fluid Bleach UV resistant Ammonia
Environmental health and issues	Halogen free
Standards	ISO 8877

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------