

Product data sheet

Characteristics

MGU3.413.12

Unica Top/Class - 1 RJ45 socket (S-One) - 2 m - Cat.5e, S/FTP - graph.



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device presentation	Mechanism
Colour tint	Graphite
Data socket type	RJ45 - 8 contacts - category 5e - transmission rate < 155 MHz
Provided equipment	Label holder Protective flap

Complementary

Communication network type	1000BASE-T
Communication port protocol	ATM 155 Mbps
Number of modules	2 modules
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	S/FTP
Organization of wire	Shielded twisted pair
Connections - terminals	Click
Fixing mode	Clip-in
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	85 mm
Height	80 mm
Embedding depth	25 mm

Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C

Ambient air temperature for storage	0...35 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	ISO 8877

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status	END-OF-SALE NOTICE
---------------------	--------------------