



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device application	Communication
Device presentation	Mechanism with central plate
Colour tint	Graphite
Data socket type	RJ45 - 4 contacts - category 6 - transmission rate < 250 MHz
Provided equipment	Protective flap Label holder

### Complementary

Communication network type	1000BASE-TX
Communication port protocol	ATM 1200 Mbps
Product destination	Duct Floor box
Number of modules	2 modules
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/UTP
Organization of wire	Unshielded twisted pair
Connections - terminals	Click
Device mounting	Flush
Fixing mode	For shield : by clips Clip-in
Installation direction	Straight
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	85 mm
Height	80 mm
Embedding depth	25 mm

## Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Window-cleaning fluid Liquid soap Alcohol Ammonia Bleach Acetone UV resistant Petrol Oil
Environmental health and issues	Halogen free
Standards	ISO 8877

## Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 4Q2016 Will be compliant on 4Q2016
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------