



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device application	Communication
Device presentation	Mechanism with central plate
Colour tint	Graphite
Data socket type	RJ45 - 4 contacts - category 6 - transmission rate < 250 MHz
Provided equipment	Protective flap Label holder

Complementary

Communication network type	1000BASE-TX
Communication port protocol	ATM 1200 Mbps
Product destination	Floor box Duct
Number of modules	2 modules
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	S/FTP
Organization of wire	Shielded twisted pair
Connections - terminals	Click
Device mounting	Flush
Fixing mode	For shield : by clips Clip-in
Installation direction	Straight
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	85 mm
Height	80 mm
Embedding depth	25 mm

Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Alcohol UV resistant Liquid soap Petrol Acetone Oil Window-cleaning fluid Ammonia Bleach
Environmental health and issues	Halogen free
Standards	ISO 8877

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------