



Main

Range of product	Unica
Range	Unica
Product or component type	USB charger
Device presentation	Mechanism
Integrated connection type	2 USB 2.0 port 5 V DC, maximum load current: 2.1 A

Complementary

Device application	Charger
Device mounting	Flush
Colour tint	Graphite
Connector type	USB 2.0
[Ue] rated operational voltage	100...240 V AC 50/60 Hz +/- 10 %
Power consumption in W	< 0.1 W
Nominal output power	10.5 W
Input power	12 W
Service life in hours	30000 h 10.5 W
Material	Casing : PC (polycarbonate) GF10 FR Internal cover : PC (polycarbonate) GF10 FR Centre plate : ABS (acrylonitrile butadiene-styrene)
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	2 x 0.75...2 x 2.5 mm ² rigid 2 x 0.75...2 x 2.5 mm ² flexible 2 x 0.75...2 x 2.5 mm ² stranded
Wire stripping length	8 mm
Product compatibility	All devices fulfilling the EN 62684 standard
Fixing mode	Screws or claws
Type of packing	Flow-pack
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	2004/108/EC EN 60950-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

2006/95/EC
EN 62684
EU directive 2002/95/EC
WEEE directive 2002/96/EC
ETSI EN 301 489-4

Height	45 mm
Width	45 mm
Depth	42 mm
Embedding depth	30.8 mm
Product weight	0.088 kg
Quantity per set	Set of 1
Sale per indivisible quantity	1

Environment

Electrical insulation class	Class II
Environmental characteristic	REACH Regulation (EC) No 1907/2006
IK degree of protection	IK04
IP degree of protection	IP20

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1725 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---