



### Main

Range	Unica
Product or component type	Data socket
Connector type	RCA
Electrical circuit type	Video Audio
Device presentation	Mechanism
Colour tint	Graphite
Type of packing	Group

### Complementary

Device mounting	Flush
Fixing mode	Clip-in
Quantity per set	Set of 10
Sale per indivisible quantity	1
Connections - terminals	Screw terminals
Clamping connection capacity	<= 1.5 mm <sup>2</sup> stranded <= 1.5 mm <sup>2</sup> flexible <= 1.5 mm <sup>2</sup> rigid
Wire stripping length	8 mm
Material	PC (polycarbonate) GF10 FR casing Thermoplastic ABS-UV stabilised centre plate
Height	45 mm
Width	22.5 mm
Depth	28 mm
Embedding depth	19 mm
Product weight	0.02 kg

### Environment

Ambient air temperature for storage	-5...50 °C
Ambient air temperature for operation	-5...40 °C
IP degree of protection	IP21
IK degree of protection	IK04

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Environmental characteristic	Petrol Alcohol Acetone Ammonia Liquid soap Window-cleaning fluid Oil Bleach UV resistant
Environmental health and issues	Halogen free

---