



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device presentation	Mechanism
Colour tint	Graphite
Data socket type	RJ45 - 8 contacts - category 6A - transmission rate < 500 MHz
Provided equipment	Protective flap Label holder

Complementary

Communication network type	10GBASE-T
Communication port protocol	ATM 1200 Mbps
Number of modules	1 module
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	S/FTP
Organization of wire	Shielded twisted pair
Connections - terminals	Click
Fixing mode	Clip-in
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	22.5 mm
Height	45 mm
Embedding depth	25 mm

Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C

Ambient air temperature for storage	0...35 °C
Environmental characteristic	Ammonia Bleach Oil Liquid soap Window-cleaning fluid Acetone UV resistant Petrol Alcohol
Environmental health and issues	Halogen free
Standards	ISO 8877

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------