



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	R-TV/SAT socket
Device presentation	Mechanism
TV socket type	Individual socket
Colour tint	Graphite

Complementary

TV connector	Male IEC 9.52 mm
SAT connector	Female IEC 9.52 mm
Path attenuation	R : < 0.8 dB @10...108 MHz TV/UHF : < 0.8 dB @470...830 MHz TV/VHF : < 0.8 dB @118...470 MHz SAT : < 1.4 dB @950...2400 MHz
DC current flow	In SAT socket
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC
Condition of use	Parallel distribution systems
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Product weight	0.073 kg
Market segment	Residential Small commercial

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Oil Bleach Ammonia UV resistant Acetone Alcohol Petrol Window-cleaning fluid Liquid soap
Environmental health and issues	Halogen free
Standards	EN 50083-2 DIN 45330 EN 50083-4 R.D. 279/1999 R.D. 1/1998 EMC directive UNE 20-523-79 (2e) DIN 45325 EN 50083-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------