



Main

| | |
|---------------------------|-------------------------------|
| Range | Unica |
| Range of product | Unica |
| Aesthetic name | Unica Top - Unica Class |
| Product or component type | R-TV/SAT socket |
| Device presentation | Mechanism |
| TV socket type | End-of-line (terminal socket) |
| Colour tint | Graphite |

Complementary

| | |
|-------------------|---|
| TV connector | Male IEC 9.52 mm |
| SAT connector | Female IEC 9.52 mm |
| Path attenuation | R : < 9 dB @10...108 MHz TV/UHF : < 9 dB @470...830 MHz TV/VHF : < 9 dB @118...470 MHz SAT : < 17 dB @950...2400 MHz |
| DC current flow | In SAT socket |
| Number per line | 1 |
| Number of modules | 2 modules |
| Material | Mechanism cover : ASA + PC |
| Condition of use | Series distribution systems |
| Fixing mode | Clip-in |
| Depth | 28 mm |
| Width | 45 mm |
| Height | 45 mm |
| Embedding depth | 18 mm |
| Product weight | 0.073 kg |
| Market segment | Small commercial Residential |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP20 |
| IK degree of protection | IK01 |
| Ambient air temperature for operation | 15...35 °C |
| Ambient air temperature for storage | 0...35 °C |
| Environmental characteristic | Acetone Oil Alcohol UV resistant Bleach Liquid soap Ammonia Petrol Window-cleaning fluid |
| Environmental health and issues | Halogen free |
| Standards | DIN 45330 EN 50083-2 DIN 45325 EN 50083-4 R.D. 1/1998 UNE 20-523-79 (2e) EN 50083-1 EMC directive R.D. 279/1999 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|