



### Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	SAT socket
Device presentation	Mechanism
TV socket type	Male terminal
Colour tint	Graphite

### Complementary

SAT connector	Male IEC 9.52 mm
Path attenuation	TV : 8 dB @5...2150 MHz
DC current flow	No
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Product weight	0.073 kg

### Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C

Environmental characteristic	Petrol UV resistant Acetone Bleach Ammonia Oil Window-cleaning fluid Alcohol Liquid soap
Environmental health and issues	Halogen free
Standards	EN 50083-2 EN 50083-1 DIN 45330 UNE 20-523-79 (2e) R.D. 1/1998 R.D. 279/1999 DIN 45325 EMC directive EN 50083-4

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------