



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	TV socket
Device presentation	Mechanism
TV socket type	Female passage
Colour tint	Graphite

Complementary

TV connector	Female IEC 9.52 mm
Branch attenuation	TV : 0.5 dB
Path attenuation	TV : 11 dB @5...862 MHz
DC current flow	No
Number per line	4
Number of modules	2 modules
Material	Mechanism cover : ASA + PC
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Product weight	0.073 kg
Market segment	Small commercial Residential

Environment

IP degree of protection	IP20
-------------------------	------

MGU3.466

IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	UV resistant Alcohol Petrol Oil Ammonia Acetone Liquid soap Window-cleaning fluid Bleach
Environmental health and issues	Halogen free
Standards	EN 50083-2 EN 50083-1 EN 50083-4 EMC directive

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------