



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	TV socket
Device presentation	Mechanism
TV socket type	Female terminal
Colour tint	Graphite

Complementary

TV connector	Female IEC 9.52 mm
Path attenuation	TV : 8 dB @5...862 MHz
DC current flow	No
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Product weight	0.073 kg
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20
IK degree of protection	IK01

MGU3.467

Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Oil Acetone Bleach Petrol UV resistant Alcohol Liquid soap Window-cleaning fluid Ammonia
Environmental health and issues	Halogen free
Standards	EN 50083-4 EMC directive EN 50083-2 EN 50083-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------