



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	TV/FM socket
Device presentation	Mechanism
TV socket type	Individual socket with galvanic insulation
Colour tint	Graphite

### Complementary

TV connector	Male IEC 9.52 mm
Radio connector	Female IEC 9.52 mm
Path attenuation	TV output : < 1 dB @40...860 MHz TV output : < 1 dB @5...40 MHz FM output : 3 dB @88...108 MHz
Number per line	1
Number of modules	2 modules
Material	Mechanism cover : ASA + PC
Condition of use	Parallel distribution systems
Fixing mode	Clip-in
Width	45 mm
Height	45 mm
Product weight	0.073 kg

### Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	0...35 °C
Environmental characteristic	Liquid soap Bleach Ammonia Acetone Oil Window-cleaning fluid Alcohol UV resistant Petrol
Environmental health and issues	Halogen free
Standards	EMC directive EN 50083-2 EN 50083-4 EN 50083-1

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------