



Main

| | |
|---------------------------|--|
| Range | Unica |
| Range of product | Unica |
| Aesthetic name | Unica Top - Unica Class |
| Product or component type | Telephone socket |
| Device presentation | Mechanism |
| Colour tint | Graphite |
| Telephone socket type | RJ11 (4 contacts): cat.3 (rate: 16 Mbit/s) |

Complementary

| | |
|---------------------------------------|---|
| Socket number | 1 |
| Number of modules | 2 modules |
| Connections - terminals | Screw terminals (twisted pair) |
| Fixing mode | Clip-in |
| Material | Mechanism cover : ABS (acrylonitrile butadiene-styrene) |
| Depth | 23 mm |
| Width | 45 mm |
| Height | 45 mm |
| Embedding depth | 12 mm |
| Product weight | 0.016 kg |
| Ambient air temperature for operation | 15...30 °C |
| Ambient air temperature for storage | 0...35 °C |
| Market segment | Residential Small commercial |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
| IK degree of protection | IK01 |

| | |
|---------------------------------|--|
| Environmental characteristic | Alcohol Liquid soap Petrol Window-cleaning fluid Bleach Oil Acetone UV resistant Ammonia |
| Environmental health and issues | Halogen free |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|