



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Telephone socket
Device presentation	Mechanism
Colour tint	Graphite
Telephone socket type	RJ12 (6 contacts): cat.3 (rate: 16 Mbit/s)

Complementary

Socket number	1
Number of modules	1 module
Connections - terminals	Screwless terminals (twisted pair)
Fixing mode	Clip-in
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	22.5 mm
Height	45 mm
Embedding depth	26 mm
Product weight	0.015 kg
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Acetone Alcohol Ammonia

Bleach
Liquid soap
Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues

Halogen free

Offer Sustainability

Sustainable offer status

Green Premium product

RoHS (date code: YYWW)

Compliant - since 0702 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH

Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Product environmental profile

Available

 [Product environmental](#)

Product end of life instructions

Need no specific recycling operations

Contractual warranty

Warranty period

18 months