



### Main

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Floor thermostat
Device application	Temperature control
Device presentation	Mechanism
Colour tint	Graphite
Provided equipment	NTC sensor with 4 m cable

### Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Load interrupting current	Resistive : 10 A
Number of modules	2 modules
Control type	Electronic controller
Function available	With temperature reduction
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Connections - terminals	Screw terminals
Status LED	Presence of voltage : 1 LED green Heating application : 1 LED red
Marking	L+N
Programmable temperature	No
Temperature setting range	5...45 °C
Measurement accuracy	0.5 °C
Material	Mechanism cover : ASA + PC
Device mounting	Flush
Fixing mode	Clip-in
Mounting height	> 1.3 m
Depth	45 mm
Width	45 mm
Height	45 mm
Embedding depth	33 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	5...45 °C
Ambient air temperature for storage	-20...60 °C
Environmental characteristic	Oil Petrol Alcohol UV resistant Liquid soap Window-cleaning fluid Acetone Ammonia Bleach
Environmental health and issues	Halogen free
Standards	EMC directive LV directive EN 607320-2-9

## Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 1Q2016 <a href="#">Will be compliant on 1Q2016</a>
REACH	Reference contains SVHC above the threshold - Go to CaP for more details <a href="#">Go to CaP for more details</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------