



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Weekly-programmable thermostat
Device presentation	Mechanism
Colour tint	Graphite

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Load interrupting current	Inductive : 5 A Resistive : 8 A
Electrical insulation class	Class II
Number of modules	2 modules
Electronic switch type	Type 1B
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Contacts type and composition	1 C/O
Connections - terminals	Screw terminals
Information displayed	Air-conditioning on Ambient room temperature 0 to 45 °C Day Time
Backup time	7 days time and program saving
Marking	L+N
Software class	Class A
Programmable temperature	Differential Frost protection Tmax Tmin
Temperature setting range	5...35 °C

Measurement accuracy	0.5 °C
Material	Mechanism cover : ASA + PC
Fixing mode	Clip-in
Mounting height	> 1.5 m
Depth	45 mm
Width	45 mm
Height	45 mm
Embedding depth	33 mm
Product weight	0.062 kg
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-5...55 °C
Relative humidity	20...85 %
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	EN 60730-2-9

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------