



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Rotary dimmer
Device presentation	Mechanism
Fixing mode	Clip-in
Dimmer application	Inductive load fluorescent lamp with 1-10 V electronic transformer
[Ue] rated operational voltage	230 V AC, 50 Hz
Number of modules	2 modules
Cover plate colour tint	Graphite

Complementary

Dimmer control	ON/OFF push
Maximum permanent current	0.2 A
Output current	<= 200 mA
Total number of wires	4
Load type	Fluorescent tube (diameter: 26...38 mm) : 1 1-10 V dimmable electronic ballast - 400 VA Fluorescent tube, 36 W : 10 1-10 V dimmable electronic ballast - 400 VA Fluorescent tube, 2 x 16 W (diameter: 26...30 mm) : 5 1-10 V dimmable electronic ballast - 400 VA External relay : 50 1-10 V electronic ballast - 400 VA
Protection type	Fuse protection
Fuse type	4 Ah (5 x 20 mm) @230 V 50 Hz
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ²
Material	Mechanism cover : ASA + PC
Standards	EN 60669-2-1
Product certifications	CE Aenor

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	54 mm
Width	45 mm
Height	45 mm
Product weight	0.104 kg
Market segment	Small commercial Residential

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Ammonia Acetone Alcohol Liquid soap Oil UV resistant Petrol Bleach
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0805 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------