



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Rotary dimmer
Device presentation	Mechanism
Fixing mode	Clip-in
Dimmer application	Resistive load Inductive load
[Ue] rated operational voltage	230 V AC, 50 Hz
Number of modules	2 modules
Cover plate colour tint	Graphite

Complementary

Dimmer control	ON/OFF push 270° rotary setting
Maximum permanent current	1.74 A
Total number of wires	2
Load type	230 V AC halogen lamp - 40...400 W 230 V AC incandescent lamp - 40...400 W Low voltage halogen lamp with ferromagnetic transformer - 40...400 VA
Protection type	Fuse protection
Fuse type	4 Ah (5 x 20 mm) @230 V 50 Hz
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ²
Connected auxiliaries	2-way switch
Material	Mechanism cover : ASA + PC
Standards	EN 60669-2-1
Product certifications	CE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	54 mm
Width	45 mm
Height	45 mm
Product weight	0.071 kg
Market segment	Small commercial Residential

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Oil Alcohol Acetone Bleach Petrol Liquid soap UV resistant Ammonia
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1345 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------