



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Push-button dimmer
Device presentation	Mechanism
Fixing mode	Clip-in
Dimmer application	Resistive load Inductive load Fan
[Ue] rated operational voltage	230 V AC, 50 Hz
Number of modules	2 modules
Cover plate colour tint	Graphite

Complementary

Dimmer control	Impulse
Maximum permanent current	1.5 A
Total number of wires	3
Load type	230 V AC incandescent lamp - 20...250 W 230 V AC halogen lamp - 20...350 W Low voltage halogen lamp with ferromagnetic transformer - 20...350 VA Low voltage halogen lamps with toroidal transformer - 20...300 VA 230 V AC fan - 20...200 W 230 V AC convector - 20...350 W
Protection type	Current protection Electronic overvoltage protection
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	$\leq 2 \times 2.5 \text{ mm}^2$
Connected auxiliaries	Maximum 5 with light indication Maximum 25 auxiliary switches
Material	Mechanism cover : ASA + PC

Standards	EN 60669-2-1
Product certifications	CE Aenor
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	47 mm
Width	45 mm
Height	45 mm
Product weight	0.078 kg
Market segment	Small commercial Residential

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Petrol Oil Alcohol Bleach Window-cleaning fluid Acetone UV resistant Liquid soap Ammonia
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------