



### Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Movement detector
Device presentation	Mechanism
Load type	Fluorescent tube (diameter: 26...38 mm) : 1 1-10 V dimmable electronic ballast - 2000 VA, cos phi: 0.9 230 V AC incandescent lamp - 2300 W 230 V AC halogen lamp - 2000 W Low voltage halogen lamp with wire-wound transformer - 1500 VA Low voltage lamps with electronic transformer - 1150 VA 230 V AC fan - 200 VA 230 V AC convector - 2300 W 230 V AC contactor - 200 VA Compact fluorescent lamp - 500 VA
Cover plate colour tint	Graphite

### Complementary

Power range	2300 W
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 18 m (PIR mounting height 1.2 m) 10 x 20 m (PIR mounting height 2.15 m)
Presence detection area	6 x 12 m (PIR mounting height 2.15 m) 5 x 10 m (PIR mounting height 1.2 m)
Detection angle	Partial 90° left or right Full 180°
Selection modes	M: manual S: slave A: automatic
Number of modules	2 modules
Type of setting	Adjustable disconnection time and brightness

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Control type	Manual override with 5 push-buttons maximum
Wiring configuration	3 wires with neutral
Light intensity adjustment	5...1000 lux
Time delay range	2 s...20 min
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Marking	L+N
Connections - terminals	Screw terminals
Material	Mechanism cover : ASA + PC
Fixing mode	Clip-in
Mounting height	> 1.2...< 2.15 m
Depth	58 mm
Width	45 mm
Height	45 mm
Embedding depth	34 mm
Product weight	0.076 kg
Market segment	Residential Small commercial

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-20...55 °C
Relative humidity	0...5 %
Environmental characteristic	Bleach Acetone UV resistant Oil Ammonia Liquid soap Alcohol Petrol Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	EN 60669-2-1

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available <a href="#">End of life manual</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------