



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica KNX
Device application	Control
Product or component type	Switch
Device presentation	Mechanism
Bus type	KNX
Switch function	1-pole 2-way
Number of rocker	2
Colour tint	Graphite

Complementary

Rated current	10 A, 24 V DC
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Actuator	Push-button
Number of modules	2 modules
Pilot light	Blue LED : 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm ² (rigid) 0...2.5 mm ² (flexible)
Material	Plastic
Surface finish	Varnished
Device mounting	Flush
Fixing mode	Clip-in
Depth	38 mm
Embedding depth	13 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	-5...45 °C
Standards	EMC directive LV directive EN 60669-1

Environment

IP degree of protection	IP20
Environmental characteristic	Alcohol Liquid soap Window-cleaning fluid Ammonia Acetone Petrol Oil UV resistant Bleach
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------