



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Product or component type	Movement detector
Device presentation	Mechanism
Cover plate colour tint	Graphite

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m(PIR mounting height 2.15m)
Detection angle	Full 180°
Number of modules	2 modules
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay range	1 s...8 min for rotary switch 1 s...255 h for ETS
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Connections - terminals	Screwless terminals
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Fixing mode	Clip-in
Mounting height	1...2.5 m
Depth	56 mm
Embedding depth	34 mm

Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach

	Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Standards	EMC directive LV directive

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------