



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica KNX
Product or component type	Room temperature control unit
Device application	Control
Device presentation	Mechanism
Colour tint	Graphite
Bus type	KNX

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Type of setting	Manual set point adjustment
Number of modules	2 modules
Device composition	4 buttons Display
Control type	Local control
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Information displayed	Day Operating mode Time Temperature
Status LED	Programming LED
Programmable temperature	No
Temperature setting range	0...40 °C
Measurement accuracy	± 1 K
Material	Plastic
Surface treatment	Varnished
Surface finish	Brilliant
Device mounting	Flush
Fixing mode	Clip-in

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting height	> 1.5 m
Depth	39 mm
Embedding depth	26 mm

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Oil Liquid soap Alcohol Ammonia Window-cleaning fluid UV resistant Acetone Petrol Bleach
Environmental health and issues	Halogen free
Standards	EMC directive LV directive

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 4Q2019 Will be compliant on 4Q2019
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------