



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Time delayed key card switch
Device application	Control
Device presentation	Mechanism
Cover plate colour tint	Graphite

Complementary

[Ue] rated operational voltage	230 V +/- 10 % AC 50 Hz
Rated current	8 A
Load type	230 V AC incandescent lamp - 1470 W 230 V AC halogen lamp - 1470 W 230 V AC fan - 1470 W 230 V AC convector - 1470 W Low voltage halogen lamp with ferromagnetic transformer - 1000 VA Low voltage halogen lamp with electronic transformer - 1470 VA Fluorescent tube ferromagnetic ballast - 1470 VA Compact fluorescent lamp - 1470 W LED lamp - 1470 W Contactor
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Number of modules	2 modules
Fuse type	Electronic
Maximum number of switchings	50000 operations
Protection type	Overvoltage protection Thermal protection
Pilot light	Amber indicator lamp
Time delay	Adjustable between 10 s and 3 mn
Marking	Vertical insertion pictogram

Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Fixing mode	Clip-in
Material	Mechanism cover : ASA + PC
Embedding depth	14 mm
Depth	Unica Top cover frame : 35 mm Unica Class cover frame : 35 mm
Width	45 mm
Height	45 mm
Product weight	0.045 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Environmental characteristic	Liquid soap Window-cleaning fluid Acetone UV resistant Oil Alcohol Petrol Ammonia Bleach
Environmental health and issues	Halogen free
Standards	EN 60669-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------