



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Wake up clock
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Graphite
Mounting height	> 1.5 m

Complementary

Information displayed	Ambient room temperature 0 to 50 °C Day Relative operating humidity 20 % to 90 % Snooze indicator Time Double alarm
Measurement accuracy	0.1 °C
Number of alarms	9 programmable alarms
Backup time	7 days time and program saving
Marking	L+N
Connections - terminals	Screw terminals
Cable cross section	<= 1.5 mm ² (flexible) <= 1.5 mm ² (rigid)
Material	Mechanism cover : ASA + PC
Standards	EN 60669-2-1
Electronic switch type	Type 1B
Software class	Class A
Electrical insulation class	Class II

Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-5...55 °C
Embedding depth	33 mm
Depth	45 mm
Width	45 mm
Height	45 mm
Product weight	0.0542 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------