

Product data sheet

Characteristics

MGU3.559.12

Unica Top/Class - rotary dimmer - 127/230 VAC -
40...400 W/VA - graphite



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Rotary dimmer
Device presentation	Mechanism
Fixing mode	Clip-in
[Ue] rated operational voltage	230 V AC, 50/60 Hz 127 V AC, 50/60 Hz
Number of modules	1 module
Cover plate colour tint	Graphite

Complementary

Dimmer control	Level by turning knob ON/OFF push
Total number of wires	2
Load type	127 V AC halogen lamp - 40...250 W 127 V AC incandescent lamp - 40...250 W 230 V AC halogen lamp - 60...400 W 230 V AC incandescent lamp - 60...400 W
Fuse type	4 Ah (5 x 20 mm) @127 V 50/60 Hz 4 Ah (5 x 20 mm) @230 V 50/60 Hz
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Material	Mechanism cover : ASA + PC
Standards	IEC 60669-1, 1998-Ed.3 + A1, 1999 IEC 60669-2-1, 2002-Ed.4
Product certifications	CE NOM/ANCE
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	50 mm
Width	22.5 mm

Height	45 mm
Product weight	0.09 kg
Market segment	Residential Small commercial

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Contractual warranty

Warranty period	18 months
-----------------	-----------