



Main

Range of product	Unica Wireless
Product or component type	Combined relay
Device presentation	Mechanism
Transmission frequency	868 MHz
[Ue] rated operational voltage	110/230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Graphite
Device composition	Wireless emitter and receiver 1 large rocker and 2 narrow rockers
Provided equipment	Set of 8 symbols

Complementary

Wiring device mounting	Flush
Operating distance	Indoor : 10...50 m Outdoor : <= 300 m
Load type	Fluorescent tube (diameter: 28...38 mm) : 1 1-10 V dimmable electronic ballast - 920 VA 230 V AC incandescent lamp - 2300 W 230 V AC halogen lamp - 2000 W 230 V AC compact fluorescent lamp - 880 VA 230 V AC fan - 690 W 230 V AC LED lamp - 880 W Low voltage halogen lamp with electronic transformer - 500 VA Low voltage halogen lamp with ferromagnetic transformer - 500 VA Low voltage halogen lamp with toroidal transformer - 500 VA Motor - 690 W
Protection type	Fuse protection
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Type of setting	Neutral position

Standards	EN 60669-1 EN 61000-6-2 EN 61000-6-3 73/23/EEC EN 60669-2-1 89/336/EEC ETSI EN 300 220 99/5/EEC ETSI EN 301 489
Ambient air temperature for operation	-5...50 °C
Relative humidity	20...95 %
Embedding depth	34 mm
Depth	46 mm
Market segment	Small commercial Residential

Environment

IP degree of protection	IP20
Environmental characteristic	Ammonia Window-cleaning fluid Alcohol Petrol Liquid soap Oil UV resistant Acetone Bleach
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------