



Main

| | |
|--------------------------------|--|
| Range of product | Unica Wireless |
| Product or component type | Combined dimmer |
| Device presentation | Mechanism |
| Transmission frequency | 868.3 MHz |
| [Ue] rated operational voltage | 230 V AC (+/- 10 %), 50 Hz |
| Number of modules | 2 modules |
| Fixing mode | Clip-in |
| Colour tint | Graphite |
| Device composition | 1 large rocker and 2 narrow rockers Wireless emitter and receiver |
| Provided equipment | Set of 8 symbols |

Complementary

| | |
|------------------------------|--|
| Wiring device mounting | Flush |
| Type of setting | Without neutral position |
| Operating distance | Indoor : 10...50 m Outdoor : <= 300 m |
| Load type | 230 V AC halogen lamp - 20...315 W 230 V AC incandescent lamp - 20...315 W Low voltage halogen lamp with electronic transformer - 20...315 VA Low voltage halogen lamp with ferromagnetic transformer - 20...315 VA Low voltage halogen lamp with toroidal transformer - 20...270 VA |
| Protection type | Damage protection from inappropriate load Overload protection Short-circuit protection Temperature rise protection |
| Connections - terminals | Screw terminals |
| Clamping connection capacity | <= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s) |
| Standards | 73/23/EEC 89/336/EEC 99/5/EEC EN 60669-1 EN 60669-2-1 EN 61000-6-2 EN 61000-6-3 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ETSI EN 300 220
ETSI EN 301 489

| | |
|---------------------------------------|---------------------------------|
| Ambient air temperature for operation | -5...35 °C |
| Relative humidity | 20...95 % |
| Embedding depth | 34 mm |
| Depth | 46 mm |
| Market segment | Residential Small commercial |

Environment

| | |
|---------------------------------|--|
| IP degree of protection | IP20 |
| Environmental characteristic | Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid |
| Environmental health and issues | Halogen free |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|