



Main

Range	Unica
Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Selector switch
Device presentation	Mechanism
Switch function	4 positions
Colour tint	Graphite

Complementary

Rated current	32 A, 250 V AC, 50/60 Hz
Power range	40...300 W 40...300 VA
Electrical durability	10000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Opening distance	> 3 mm
Actuator	Rotary
Number of modules	2 modules
Connections - terminals	Screw terminals
Cable cross section	0...6 mm ² (flexible) 0...6 mm ² (rigid)
Material	Mechanism cover : ASA + PC
Marking	1
Fixing mode	Clip-in
Width	45 mm
Height	45 mm

Depth	30 mm
Product weight	0.027 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EN 60669-1 LV directive EMC directive

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Window-cleaning fluid Bleach Petrol Ammonia Acetone Oil Liquid soap Alcohol UV resistant
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------