



### Main

Range of product	Unica
Range	Unica
Device application	Control
Product or component type	Miniature circuit-breaker switch
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Poles description	1P + N
Rated current	10 A, 230 V AC
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	White

### Complementary

Marking	I-O
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Trip unit technology	Thermal-magnetic
Breaking capacity	3 kA
Earth-leakage sensitivity	10 mA
Earth-leakage protection class	Class A
Material	Mechanism cover : ASA + PC
Standards	EN 60898 UNE 60898
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	38 mm
Depth	54 mm

Width	45 mm
Height	45 mm
Product weight	0.089 kg

## Environment

IK degree of protection	IK01
IP degree of protection	IP41
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------