



## Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Fuse holder
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Rated current	10 A, 230 V AC, 50/60 Hz
Number of modules	1 module
Fixing mode	Clip-in
Colour tint	Graphite

## Complementary

Fuse type	Cylindrical (6 x 32 mm)
Provided equipment	Fuse not supplied
Connections - terminals	Screw terminals
Cable cross section	0...4 mm <sup>2</sup> (rigid) 0...4 mm <sup>2</sup> (flexible)
Material	Mechanism cover : ASA + PC
Standards	UNE 60127
Product certifications	ES.ME01.B02318 AC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	30.8 mm
Depth	43.5 mm
Width	22.5 mm
Height	45 mm
Product weight	0.0278 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Liquid soap Window-cleaning fluid Oil Petrol UV resistant Ammonia Alcohol Bleach Acetone
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------