

Product data sheet

Characteristics

MGU3.631.12

Unica Top/Class - fuse holder - 16 A, 250 VAC - cyl. 8.3x31.5 mm - 2 m - graph.



Main

Range	Unica
Range of product	Unica
Device application	Mounting
Product or component type	Fuse holder
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Rated current	16 A, 230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Graphite

Complementary

Fuse type	Cylindrical (8.3 x 31.5 mm)
Provided equipment	Fuse not supplied
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² (rigid) 0...4 mm ² (flexible)
Material	Mechanism cover : ASA + PC
Standards	EN 60269
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	44 mm
Width	45 mm
Height	45 mm
Product weight	0.0292 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil Acetone

Window-cleaning fluid
Petrol
Liquid soap
UV resistant
Alcohol
Bleach
Ammonia

Environmental health and issues

Halogen free

Offer Sustainability

RoHS (date code: YYWW)

Compliant - since 0702 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH

Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Contractual warranty

Warranty period

18 months
