



Main

Range of product	Unica
Range	Unica
Device application	Control
Product or component type	Miniature circuit-breaker switch
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Poles description	1P
Rated current	16 A, 230 V AC
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	White

Complementary

Marking	I-O
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Trip unit technology	Thermal-magnetic
Breaking capacity	1.5 kA
Earth-leakage sensitivity	10 mA
Earth-leakage protection class	Class A
Material	Mechanism cover : ASA + PC
Standards	UNE 60898 EN 60898
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	38 mm
Depth	54 mm

Width	22.5 mm
Height	45 mm
Product weight	0.064 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP41
Environmental characteristic	Alcohol Liquid soap Oil Acetone Bleach Window-cleaning fluid Petrol Ammonia
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------