

Product data sheet

Characteristics

MGU3.710.12

Unica Top/Class - methane gas detector - 12 V
AC/DC - 2 m - graphite



Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product name	Unica Top - Unica Class
Product or component type	Methane gas detector
Device presentation	Mechanism
Cover plate colour tint	Graphite
Provided equipment	Label Test button

Complementary

[Ue] rated operational voltage	12 V
Current consumption	130 mA
Number of modules	2 modules
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Cable cross section	<= 1.5 mm ² (flexible) <= 1.5 mm ² (rigid)
Operating distance	From the ceiling for methane gas detectors : 50 cm
Acoustic level	85 dB @ 1 m
Service life	5 yr 0 yr
Pilot light	Alarm indication : red LED Power indication : green LED Stabilization or malfunction indications : amber LED
Fixing mode	Clip-in
Depth	50 mm
Embedding depth	33 mm

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Acetone Alcohol

Ammonia
Bleach
Liquid soap
Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues	Halogen free
Ambient air temperature for operation	5...40 °C
Standards	EMC directive LV directive EN 50194

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
