



Main

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product name	Unica Top - Unica Class
Product or component type	Flood detector
Device application	Sensitive control application
Device presentation	Mechanism
Cover plate colour tint	Graphite
Provided equipment	Test button

Complementary

Range compatibility	Unica Unica Top - Unica Class flood detector
[Ue] rated operational voltage	12 V
Current consumption	63 mA
Number of modules	2 modules
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Cable cross section	<= 1.5 mm ² (flexible) <= 1.5 mm ² (rigid)
Acoustic level	85 dB @ 1 m
Service life	0 yr 5 yr
Pilot light	Alarm indication : red LED Power indication : green LED
Device mounting	Built-in
Fixing mode	Clip-in
Depth	50 mm
Width	45 mm
Height	45 mm
Embedding depth	33 mm

Environment

IP degree of protection	IP20
-------------------------	------

IK degree of protection	IK01
Environmental characteristic	Oil Alcohol Liquid soap Acetone Window-cleaning fluid Ammonia Bleach Petrol UV resistant
Environmental health and issues	Halogen free
Ambient air temperature for operation	5...40 °C
Standards	LV directive EMC directive EN 50194

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 4Q2019 Will be compliant on 4Q2019
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------