



### Main

Range of product	Unica
Range	Unica
Device application	Lighting
Product or component type	Flat indicator lamp
Aesthetic name	Unica Top - Unica Class
Product compatibility	Unica neon bulb
Device presentation	Mechanism
[Ue] rated operational voltage	220 V AC, 50/60 Hz
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	Graphite

### Complementary

Light block colour	Orange
Bulb type	Neon lamp
Connections - terminals	Screw terminals
Cable cross section	<= 2.5 mm <sup>2</sup> (flexible) <= 2.5 mm <sup>2</sup> (rigid)
Material	Mechanism cover : ASA + PC
Standards	EMC directive LV directive
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	44 mm
Width	22.5 mm
Height	45 mm
Product weight	0.0645 kg

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Window-cleaning fluid Oil Acetone UV resistant Ammonia Alcohol Petrol Liquid soap Bleach
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------