



Main

Range	Unica
Aesthetic name	Unica
Product or component type	Emergency light
Device presentation	Complete product
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50 Hz
Number of modules	2 modules
Fixing mode	Clip-in

Complementary

Condition of use	Battery and bulb cannot be replaced
Light block colour	Green
Bulb type	LED
Bulb lifespan	400 h
Illuminance	45 lux 25 cm
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Charging time	24 h
Electrical durability	500 cycles
Material	Mechanism cover : transparent plastic
Standards	UNE 20062-93 EN 60598-2-22 LV directive EMC directive UNE 60598-2-22
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm
Depth	44 mm

Width	45 mm
Height	45 mm
Product weight	0.085 kg
Market segment	Small commercial Residential

Environment

IP degree of protection	IP20
Environmental characteristic	Petrol Alcohol Liquid soap Ammonia Bleach Oil Acetone UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------