



### Main

Range	Unica
Aesthetic name	Unica
Product or component type	Autonomous pilot lamp
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Product compatibility	Unica telecommand unit

### Complementary

Light block colour	Green Yellow
Bulb type	LED
Bulb lifespan	400 h
Luminous flux	2 lm
Supply	Rechargeable batteries
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Charging time	24 h
Material	Mechanism cover : transparent plastic
Standards	EMC directive UNE 20062-93 EN 60598-2-22 LV directive UNE 60598-2-22
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm

Depth	44 mm
Width	45 mm
Height	45 mm
Product weight	0.063 kg

## Environment

IK degree of protection	IK07
IP degree of protection	IP20
Environmental characteristic	Alcohol UV resistant Petrol Ammonia Window-cleaning fluid Liquid soap Acetone Bleach Oil
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------