



### Main

Range of product	Unica
Range	Unica
Device application	Signalling
Product or component type	Buzzer
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Graphite
Market segment	Residential Small commercial

### Complementary

Current consumption	40 mA
Type of setting	Volume can be adjusted using a screw
Operating time	0...60 ms
Connections - terminals	Screw terminals
Acoustic level	Between 76 and 80 dB
Cable cross section	0.75...1.5 mm <sup>2</sup> (flexible) 0.75...1.5 mm <sup>2</sup> (rigid)
Material	Mechanism cover : ASA + PC
Standards	EMC directive LV directive
Product certifications	CE
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm

Depth	42 mm
Width	45 mm
Height	45 mm
Product weight	0.048 kg

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------