



Main

Range of product	Unica
Range	Unica
Accessory / separate part category	Cabling accessory
Product or component type	Cable outlet
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Number of modules	1 module
Fixing mode	Clip-in
Provided equipment	Anti-tug clamps
Colour tint	Graphite

Complementary

Range compatibility	Unica
Rated current	16 A
Connections - terminals	Screw terminals
Clamping connection capacity	<= 3 x 2.5 mm ² for flexible cable(s) <= 3 x 2.5 mm ² for rigid cable(s)
Material	Mechanism cover : ABS (acrylonitrile butadiene-styrene)
Product certifications	ES.ME01.B02319 AC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Width	45 mm
Height	22.5 mm
Product weight	0.0145 kg

Environment

IK degree of protection	IK01
-------------------------	------

MGU3.860

IP degree of protection	IP40
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------