



Main

Range of product	Unica
Range	Unica
Accessory / separate part category	Cabling accessory
Product or component type	Cable outlet
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Number of modules	2 modules
Fixing mode	Clip-in
Provided equipment	Anti-tug clamps
Colour tint	Graphite

Complementary

Range compatibility	Unica
Rated current	16 A
Connections - terminals	Screw terminals
Clamping connection capacity	<= 3 x 2.5 mm ² for flexible cable(s) <= 3 x 2.5 mm ² for rigid cable(s)
Material	Mechanism cover : ASA + PC
Product certifications	ES.ME01.B02319 AC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Width	45 mm
Height	45 mm
Product weight	0.0178 kg
Market segment	Small commercial Residential

MGU3.862

Environment

IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	Liquid soap Oil Ammonia Acetone Petrol Bleach UV resistant Window-cleaning fluid Alcohol
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------