



Main

| | |
|---------------------------|-------------------------------|
| Range | Unica |
| Product or component type | Sensor for flood detector |
| Device application | Sensitive control application |
| Device presentation | Complete mechanism |
| Cover plate colour tint | White |

Complementary

| | |
|--------------------------------|---|
| Range compatibility | Unica Unica Top - Unica Class flood detector |
| [Ue] rated operational voltage | 12 V |
| Connections - terminals | Screwless terminals |
| Cable cross section | <= 1.5 mm ² (flexible) <= 1.5 mm ² (rigid) |
| Device mounting | Surface |
| Depth | 50 mm |
| Width | 45 mm |
| Height | 45 mm |

Environment

| | |
|---------------------------------------|--|
| IP degree of protection | IP20 |
| IK degree of protection | IK01 |
| Environmental characteristic | Liquid soap Acetone UV resistant Bleach Window-cleaning fluid Oil Alcohol Ammonia Petrol |
| Environmental health and issues | Halogen free |
| Ambient air temperature for operation | 5...40 °C |
| Standards | EN 50194 EMC directive LV directive |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

| | |
|-------------------------------|--|
| RoHS (date code: YYWW) | Will be compliant on 4Q2019 Will be compliant on 4Q2019 |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
