



### Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Basic Unica Colors
Number of gangs	1 gang
Number of modules	2 modules
Fixing mode	Screws
Colour tint	White

### Complementary

Provided equipment	Fixing frame
Material	Cover frame : ASA + PC Decorative frame : ASA + PC Fixing frame : PBT (polybutylene terephthalate) GF30
Standards	EN 60669-1
Width	60 mm
Height	55.8 mm
Depth	13.5 mm
Product weight	0.018 kg

### Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Ammonia Bleach Alcohol Oil

Petrol  
Liquid soap  
UV resistant  
Acetone  
Window-cleaning fluid

---

Environmental health and issues	Halogen free
---------------------------------	--------------

---

### Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---

---

REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
-------	--

---

Product environmental profile	Available <a href="#">Product environmental</a>
-------------------------------	--

---

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---