



### Main

Range of product	Unica
Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Top
Number of gangs	2 gangs horizontal
Number of modules	2 x 6 modules
Fixing mode	Screws
Colour tint	Bright chrome
Decoration colour	Aluminium

### Complementary

Provided equipment	Fixing frame
Material	Intermediate part : ASA + PC Cover frame : zamak Fixing frame : LATER 4 G30V0 2307Y1 GRIS
Standards	EN 60669-1
Width	195 mm
Height	175 mm
Depth	16 mm
Distance between centers	69 mm
Product weight	0.344 kg
Market segment	Residential Small commercial

### Environment

IK degree of protection	IK01
IP degree of protection	IP20

MGU49.426

Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------