



Main

Range of product	Unica
Range	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Switch
Device presentation	Mechanism with zamak fixing frame
Switch function	2 x 1-pole 1-way
Number of rocker	2
Provided equipment	Internal power connection
Colour tint	Graphite

Complementary

Rated current	10 AX, 250 V AC, 50/60 Hz
Maximum switching current	10 mA
Electrical durability	10000 cycles
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	2 x 1 module
Pilot light	Blue LED : 0.15 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm ² (rigid) 0...2.5 mm ² (flexible)
Material	Mechanism cover : ASA + PC Fixing frame : zamak Fixing frame : PBT (polybutylene terephthalate) GF30

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Surface finish	Untreated
Fixing mode	Screws
Width	70.9 mm
Height	70.9 mm
Depth	34 mm
Embedding depth	24 mm
Product weight	0.074 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	LV directive EN 60669-1 EMC directive
Product certifications	FR.ME63.B02736

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Bleach Window-cleaning fluid Acetone Alcohol Oil UV resistant Ammonia Petrol Liquid soap
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------