



### Main

Range of product	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Shaver socket
Product compatibility	Uninterruptible power supply
Device presentation	Mechanism with fixing frame
Rated power in VA	20 VA
Input voltage	240 V, 50 Hz
Output voltage	115...240 V AC, 50/60 Hz
Number of modules	3 modules
Fixing mode	Clip-in
Cover plate colour tint	White

### Complementary

Connections - terminals	Screw terminals
Cable cross section	<= 4 mm <sup>2</sup> (flexible) <= 4 mm <sup>2</sup> (rigid)
Minimum load breaking capacity	100 operations 1.25 In and 1.1 Un, cos phi: 0.6
Electrical durability	10000 cycles (cos phi: 0.8)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Quantity per set	Set of 1
Standards	IEC 60884-1 SI 32 NOM-003-SCFI-2000 UNE 20315-1-2 BS 1363-1 BS 546:1950 VDE 0620-1 NFC 61-314
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Embedding depth	40 mm
Depth	52 mm
Market segment	Residential Small commercial

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Alcohol Acetone Bleach Ammonia Petrol UV resistant Oil Liquid soap Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------